



Installation Instructions for JCHSR98
Jeep Cherokee Sport 98+
120L Replacement Tank

1. Drain and remove the original tank. Remove the fuel pump.
2. The float arm on the sender unit needs to be lengthened by 70mm. The rod in the fitting kit is 90mm long which allows for a 10mm overlap on the join. Install the fuel pump/sender unit into new tank and check full/empty range of the float arm. Use the new hold down ring and socket head screws to lock pump into position.
3. Lift the tank into position and secure with the new straps and original bolts
4. Connect all of the remaining hoses and fittings. Cable tie all hoses and wiring neatly in place. Check all clearances. Fill tank with fuel and check all hoses and fittings.

NOTE: USE A HIGH QUALITY SEALER ON ALL JOINS AND FITTINGS E.G. PERMATEX 3J



FITTING KIT CONTENTS JCHSR98

Brass:	Electrical:
○	○
Bolts / Nuts:	Misc Parts:
<ul style="list-style-type: none"> ○ 6 x M5 x 6mm socket head screws ○ 6 x M5 x 10mm washers 	<ul style="list-style-type: none"> ○ 1 x Pump Hold Down Ring ○ 1 x Roll Over Valve ○ 1 x Roll Over Valve Grommet ○ 1 x 2.5mm Rod @ 90mm ○ 2 x Fuel Tank Straps
Hose Clamps:	Cable Ties:
○ :	○
Sender:	Pumps & Filters:
○	○
Hose:	2 Pages of Fitting Instructions Consisting of:
○	<ul style="list-style-type: none"> ○ 1 x Page Fitting Instructions ○ 1 x Page Fitting Kit Contents

Kit Packed By _____

Checked By _____