



**Installation Instructions for JGCHR98
Jeep Grand Cherokee 98 Onwards
120L Replacement Tank**

1. Drain and remove original tank. Remove fuel pump.
2. Float arm on sender unit needs to be lengthened by 70mm. The rod in the fitting kit is 90mm long allowing for a 10mm overlap on the join. Install fuel pump/sender unit into new tank and check full/empty range of float arm. Use new hold down ring and socket head screws to lock pump in position.
3. Lift tank into position and secure with new straps and original bolts
4. Connect all remaining hoses and fittings. Cable tie all hoses and wiring neatly in place. Check all clearances. Fill tank with fuel and check all hoses and fittings.

NOTE: Use high quality sealer on all joins and fittings e.g. PERMATEX 3J



FITTING KIT CONTENTS JGCHR98

Brass	Electrical
Bolts / Nuts	Misc Parts
<ul style="list-style-type: none">○ 6 x M5 x 6mm socket head screws○ 6 x M5 x 10mm washers	<ul style="list-style-type: none">○ 1 x pump hold down ring○ 1 x roll over valve○ 1 x roll over valve grommet○ 1 x 2.5mm rod @ 90mm○ 2 x fuel tank straps
Hose Clamps	Cable Ties
Hose	Sender
Filters	Instruction Pages
	2 pages fitting instructions consisting of: <ul style="list-style-type: none">○ 1 x page fitting kit contents○ 1 x pages fitting instructions

Kit Packed By _____

Kit Checked By _____