



Installation Instructions for TH105SR
Toyota Hilux Single Cab 105/106
130L Replacement Tank

1. Remove rear section of drive shaft taking care to mark splines for later refitting. Loosen rear section of exhaust system. Drain and remove original tank.
2. Remove fuel sender unit and fuel pick up from original tank and position sender unit in new tank. Adjust float arm length to ensure accurate fuel gauge. Fit sender unit to tank using OEM screws. Fit fuel pick up unit to tank using OEM screws. Screw brass fittings into tank and attach hoses to respective fittings as per diagram.
3. The driver's side front shackle may need to be cut to length of shackle bolt nut.
4. Lift tank into position and bolt in place using new bolts provided. Connect all lines and sender unit wires.
5. Refit drive shaft and tighten exhaust system.
6. Fill with fuel and check all hoses and fittings for leaks.



FITTING KIT CONTENTS TH105SR

Brass:	Electrical:
<ul style="list-style-type: none"> ○ 1 x P3 1/2 x 1/4 (12mm Hose Barb Straight) ○ 1 x P3 1/4 x 1/4 (6mm Hose Barb Straight) 	
Bolts / Nuts:	Misc Parts:
<ul style="list-style-type: none"> ○ 1 x M10 x 30mm Bolt ○ 1 x M10 Nyloc Nut ○ 1 x M10 x 21 x 16g Washer ○ 6 x M8 x 25mm Bolt ○ 1 x M8 Nyloc Nut ○ 6 x M8 Spring Washers ○ 6 x M8 x 25 x 16g Washers 	
Hose Clamps:	Cable Ties:
<ul style="list-style-type: none"> ○ 6 x 1/4" Hose Clamps ○ 1 x 1/2" Hose Clamp ○ 1 x 2" Hose Clamp 	
Sender:	Pumps & Filters:
Hose:	3 Pages of Fitting Instructions Consisting of:
<ul style="list-style-type: none"> ○ 1 x 6mm Fuel Hose @ 700mm ○ 1 x 6mm Fuel Hose @ 850mm ○ 1 x 8mm Fuel Hose @ 900mm 	<ul style="list-style-type: none"> ○ 1 x Page Fitting Instructions ○ 1 x Page Fitting Kit Contents ○ 1 x Page Fittings Diagram

Kit Packed By _____

Checked By _____

TOYOTA HILUX S/CAB PART NO TH105S
130LT REPLACEMENT TANK
FITTING INSTRUCTIONS

