

FITTING KIT CONTENTS TLCP120AX

Brass:	Electrical:
o 1 x P6 5/16 x 1/4 Elbow	o 1 x LRA-PG210 Switch/Gauge
o 1 x P6 1/2 x 1/4 Elbow	o 1 x 3mm Two Core x 5m
o 1 X P3 5/16 x 1/8 Straight	o 1 x 4mm Single Core Blue Wire @300mm
o 1 x P3 x 1/2 x 1/4 Straight	o 1 x 5AMP fuse
o 1 x P14 1/4 Tee	o 1 x Fuse Holder
	o 2 x Fuse Holder Terminals
	o 2 x Red Earth Eye
	○ 1 x Red Insulated Terminal
	o 3 x Heat Shrink @ 30mm
Bolts / Nuts:	Misc Parts:
o 4 x M8 x 25mm Bolt	o 1 x 35mm x 35mm x 32mm Tee Piece Filler
o 2 x M10 x 90mm Bolt	○ 1 x Roll Over Valve
o 4 x M12 x 30mm Bolt Fine 1.25	o 1 x LRA-FTG-2
pitch	
o 4 x M8 x 25mm Flat Washer	
o 4 x M8 Spring	
o 4 x M10 x 25mm Flat Washer	
o 2 x M10 Spring	
o 2 x M10 Nyloc Nut	
o 2 x M10 Nut	
o 4 x M12 Spring Washers	
o 4 x M12 x 30 mm Washer	
Hose Clamps:	Hose:
o 10 x 1/4 Hose Clamp	o 1 x 6mm Fuel Hose @ 1000mm long
o 4 x 1/2 Hose Clamp	o 1 x 8mm Fuel Hose @ 800mm long
o 6 x 1 1/4 Hose Clamp	o 2 x 12mm Fuel Hose @ 300mm long
	o 2 x 35mm Fuel Hose @ 140mm long
	o 1 x 32mm Fuel Hose @ 80mm long
Pumps & Filters:	Cable Ties:
o 1 x Fuel Pump & Filter	o 8 x 7" Cable Tie
o 1 x Fuel Pump Mounting Plate	

Sender:	4 Pages of Fitting Instructions Consisting of:
o 1 x 0-900HM Sender C/W	o 2 x Page Fitting Kit Contents
300mm Earth, Installed Using:	o 1 x Page Picture Hose and fitting Layout
- 5 x M5 x 10mm Pan Heads	o 1 x Page Wiring Diagram WDSGPG210
- 5 x M5 Spring Washers	

Kit Packed By	Checked By
---------------	------------



